

R cheat sheet

Copied in part from <https://cran.r-project.org/doc/contrib/Short-refcard.pdf>

Getting help

?**topic** gives documentation on given topic.

Input & output

install.packages("name") installs the given package to this computer

library(name) load add-on packages

read.table(file) reads a file in table format and creates a data frame from it

write.table(x, file="<file>") saves data frame to file

setwd(), getwd() sets and returns the working directory

Data creation

c(...) generic function to combine arguments into a vector

from:to generates a sequence

seq(from, to) generates a sequence by= specifies increment;

length= specifies desired length

seq(along=x) generates 1, 2, ..., length(along)

rep(x, times) replicate x times; use each= to repeat "each" element of x each times

data.frame(...) create a data frame of the named or unnamed arguments; shorter vectors are recycled to the length of the longest

list(...) create a list of the named or unnamed arguments

factor(x, levels=) encodes a vector x as a factor

gl(n, k, labels=<labels>) generate levels (factors) by specifying the pattern of their levels; n is the number of levels, and k is the number of replications

rbind(...) combine arguments by rows for matrices, data frames, and others

cbind(...) idem by columns

Slicing & extracting data

Indexing vectors

x[n] nth element

x[-n] all but the nth element

x[1:n] first n elements

x[-(1:n)] elements from n+1 to the end

x[c(1,4,2)] specific elements

x["name"] element named "name"

x[x > 3] all elements greater than 3

x[x > 3 & x < 5] all elements between 3 and 5

x[x %in% c("a", "and", "the")] elements in the given set

Indexing lists

x[n] list with elements n

x[[n]] nth element of the list

x[["name"]] element of the list named "name"

x\$name idem

Indexing data frames

x[i, j] element at row i, column j

x[i,] row i

x[, j] column j

x[, c(1,3)] columns 1 and 3

x["name",] row named "name"

x[["name"]] column named "name"

x\$name idem

Variable conversion

as.array(x), as.data.frame(x), as.numeric(x), as.logical(x), as.complex(x), as.character(x), ... convert type; for a complete list, use **methods(as)**

Variable information

is.na(x), is.null(x), is.array(x), is.data.frame(x), is.numeric(x), is.complex(x), is.character(x), ... test for type; for a complete list, use **methods(is)**

length(x) number of elements in x

dim(x) retrieve or set the dimension of an object

nrow(x) number of rows

ncol(x) number of columns

str(object) display the internal *str*ucture of an R object

summary(object) gives a "summary" of object, usually a statistical summary, but it is generic, meaning it has different operations for different classes

complete.cases(x) gives a logical vector indicating which cases (rows of a dataframe) have no missing values

class(x) gives the data type of x

Data selection and manipulation

with(x, ...) execute statements within a local environment

rev(x) reverses the elements of x

sort(x) sorts the elements of x in increasing order; to sort in decreasing order: **rev(sort(x))**

order(x) returns a permutation which rearranges its first argument into ascending or descending order

cut(x, breaks) divides x into intervals (factors)

match(x, y) returns a vector of the same length than x with the elements of x which are in y (NA otherwise)

which(expr on x) returns a vector of the indices of x if the comparison operation is true

na.omit(x) suppresses the observations with missing data (NA) (suppresses the corresponding line if x is a matrix or a data frame)

unique(x) if x is a vector or a data frame, returns a similar object but with the duplicate elements suppressed

table(x) returns a table with the numbers of the different values of x (typically for integers or factors)

subset(x, ...) returns a selection of x with respect to criteria (...); if x is a data frame, the option **select** gives the variables to be kept (or dropped using a minus sign)

sample(x, size) sample randomly from x

Math & Descriptive statistics

max(x) maximum of the elements of x

min(x) minimum of the elements of x

range(x) gives **c(min(x), max(x))**

sum(x) sum of the elements of x

mean(x) mean of the elements of x

median(x) median of the elements of x

quantile(x, probs=) sample quantiles corresponding to the given probabilities (defaults to 0, .25, .5, .75, 1)

IQR(x) interquartile range

var(x) or **cov(x)** variance of the elements of x (calculated on n-1);

sd(x) standard deviation of x

round(x, n) rounds the elements of x to n decimals

log(x, base) computes the logarithm of x with base base

scale(x) if x is a matrix, centers and reduces the data

Advanced data processing

apply(X, INDEX, FUN=) a vector or array or list of values obtained by applying function FUN to margins (INDEX) of X

lapply(X, FUN) apply FUN to each element of the list X; **sapply** is a wrapper for lapply that tries to simplify the result.

tapply(X, INDEX, FUN=) apply FUN to each cell of a ragged array given by X with indexes INDEX

merge(a, b) merge two data frames by common columns or row names

aggregate(x, by, FUN) splits the data frame x into subsets, computes summary statistics for each, and returns the result in a convenient form; by is a list of grouping elements, each as long as the variables in x

Strings

paste(...) concatenate vectors after converting to character
substr(x, start, stop) substrings in a character vector; can also assign, as `substr(x, start, stop) <- value`
strsplit(x, split) split x according to the substring split
grep(pattern, x) searches for matches to pattern within x; see ?regex
gsub(pattern, replacement, x) replacement of matches determined by regular expression matching; **sub()** is the same but only replaces the first occurrence.
tolower(x) convert to lowercase
toupper(x) convert to uppercase
x %in% table a logical vector of the matches for the elements of x among table
nchar(x) number of characters

Plotting

plot(x) plots the values of x (on the y-axis) ordered on the x-axis
plot(x, y) bivariate plot of x (on the x-axis) and y (on the y-axis)
hist(x) histogram of the frequencies of x
barplot(x) histogram of the values of x
pie(x) circular pie-chart
boxplot(x) "box-and-whiskers" plot
stripplot(x) plot of the values of x on a line (an alternative to boxplot() for small sample sizes)
coplot(x~y | z) bivariate plot of x and y for each value or interval of values of z
pairs(x) if x is a matrix or a data frame, draws all possible bivariate plots between the columns of x
qqnorm(x) quantiles of x with respect to the values expected under a normal law
qqplot(x, y) quantiles of y with respect to the quantiles of x
matplot(x, y) plot the columns of one matrix against the columns of another, or the columns of a matrix (or dataframe).

The following parameters are common to many plotting functions:

add=FALSE if TRUE superposes the plot on the previous one
axes=TRUE if FALSE does not draw the axes and the box
type="p" specifies the type of plot, "p": points, "l": lines, "b": points connected by lines, "o": id. but the lines are over the points, "h": vertical lines, "s": steps, the data are represented by the top of the vertical lines, "S": id. but the data are represented by the bottom of the vertical lines
xlim=, ylim= specifies the lower and upper limits of the axes
xlab=, ylab= annotates the axes with labels
main= main title ; **sub=** sub-title

Low-level plotting commands

points(x, y) adds points (the option type= can be used)
lines(x, y) id. but with lines
text(x, y, labels, ...) adds text given by labels at coordinates (x,y)
abline(a,b) draws a line of slope b and intercept a
abline(h=y) draws a horizontal line at ordinate y
abline(v=x) draws a vertical line at abscissa x
abline(lm.obj) draws the regression line given by lm.obj
legend(x, y, legend) adds the legend at the point (x,y) with the symbols given by legend
title() adds a title and optionally a sub-title
axis(side, vect) adds an axis

Graphical parameters

These can be set globally with `par(...)`; many can be passed as parameters to plotting commands. Type `?par` for more info
bg specifies the colour of the background (ex. : `bg="red"`, `bg="blue"`, ... the list of the 657 available colours is displayed with `colors()`)
bty controls the type of box drawn around the plot, allowed values are: "o", "l", "7", "c", "u" ou "]" (the box looks like the corresponding character); if `bty="n"` the box is not drawn

cex a value controlling the size of texts and symbols with respect to the default; the following parameters have the same control for numbers on the axes, `cex.axis`, the axis labels, `cex.lab`, the title, `cex.main`, and the sub-title, `cex.sub`
col controls the color of symbols and lines; use color names: "red", "blue" see `colors()` or as "#RRGGBB"; see `rgb()`, `hsv()`, `gray()`, and `rainbow()`; as for `cex` there are: `col.axis`, `col.lab`, `col.main`, `col.sub`
font an integer which controls the style of text; as for `cex` there are: `font.axis`, `font.lab`, `font.main`, `font.sub`
las an integer which controls the orientation of the axis labels
lty controls the type of lines
lwd a numeric which controls the width of lines, default 1
mar a vector of 4 numeric values which control the space between the axes and the border of the graph: `c(bottom, left, top, right)`
mfcol a vector of the form `c(nr,nc)` which partitions the graphic window as a matrix of nr lines and nc columns, the plots are then drawn in columns
mfrow id. but the plots are drawn by row
pch controls the type of symbol, either an integer between 1 and 25, or any single character within ""

Optimization and model fitting

lm(formula) fit linear models
loess(formula) fit a polynomial surface using local fitting. Many of the formula-based modeling functions have several common arguments: `data=` the data frame for the formula variables, `subset=` a subset of variables used in the fit, `na.action=` action for missing values: "na.fail", "na.omit", or a function. The following generics often apply to model fitting functions:
predict(fit, ...) predictions from fit based on input data

Statistics

aov(formula) analysis of variance model
anova(fit, ...) analysis of variance (or deviance) tables for one or more fitted model objects
density(x) kernel density estimates of x
binom.test(), **pairwise.t.test()**, **power.t.test()**, **prop.test()**, **t.test()**, ... use `help.search("test")`

Distributions

rnorm(n, mean=0, sd=1) Gaussian (normal)
rbinom(n, size, prob) binomial
All these functions can be used by replacing the letter r with d, p or q to get, respectively, the probability density (`dfunc(x, ...)`), the cumulative probability density (`pfunc(x, ...)`), and the value of quantile (`qfunc(p, ...)`), with $0 < p < 1$.
NB: There are many more distributions!

Programming

function(arglist) expr function definition
return(value)
if(cond) expr
if(cond) cons.expr else alt.expr
for(var in seq) expr loop over seq and put the elements in var
while(cond) expr loop while condition is true
break breaks out of loop iteration
next goes to next loop iteration
Use braces {} around statements
ifelse(test, yes, no) a value with the same shape as test filled with elements from either yes or no